Brancoforte Paints

BRANCO FORTE Paints

PRIMER PARA PAREDES ALPHA CEMENT (ZARCÃO)

ALPHA CEMENT PRIMER



Exterior

Interior

High Coverage
Alta Cobertura

Economical
Económico

Water Thinnable
Diluível em Água

Easy Brushability
Fácil de Pincelar

Fabricado na Índia
Made in India

PRIMER PARA PAREDES ALPHA CEMENT (ZARCÃO)

ALPHA CEMENT PRIMER

Sobre o Produto:
O ALPHA é um primário à base de água, ideal como primeira demão em todos os tipos de superfícies de cimento e alvenaria.

Condições de Aplicação:
A superfície deve estar limpa, seca e isenta de pó, óleo e gordura. Aplique 1–2 demãos, certificando-se de que a primeira demão está completamente seca antes de aplicar a segunda.

Ferramentas de Aplicação:
Pincel, rolo, pistola de pintura

Instruções de Aplicação:
1. Dilua com água limpa até 100% e misture bem, com um movimento circular ascendente, antes de usar.
2. Aplique 1–2 demãos com pincel, rolo ou pistola.
3. Deixe secar completamente. O tempo médio de secagem é de 4 a 6 horas.
4. Depois de seco, aplique a tinta de acabamento adequada.

Durante a Pintura:
Garanta uma ventilação adequada. Mantenha o chão e os móveis cobertos.

Rendimento:
Rendimento aproximado: 8–10 m²/L por demão.

Eliminação:
Não despeje restos de tinta em ralos ou esgotos. Guarde a tinta não utilizada num recipiente coberto e bem fechado.

Segurança e Primeiros Socorros:

Em Caso de Derrame e Eliminação:
Escorregadio quando derramado. Limpe imediatamente. Não despeje em ralos nem em cursos de água.

Primeiros Socorros:
Em caso de intoxicação, contacte os serviços de emergência locais.

Contacto com os Olhos:
Em caso de contacto com os olhos, mantenha-os abertos e lave com água corrente durante, pelo menos, 15 minutos.

Contacto com a Pele:
Em caso de contacto com a pele, retire a roupa contaminada e lave a pele com água.

Em Caso de Ingestão:
Enxague a boca com água. NÃO provoque o vómito.

About the Product:
ALPHA is a water-based primer, perfect as the first coat for all types of cement and masonry surfaces.

Application Condition:
Surface must be clean, dry and free from dust, oil and grease. Apply 1–2 coats, ensuring that the first coat is completely dry before applying the second.

Application Tools:
Brush, roller, spray

Application Instructions:
1. Dilute with clean water up to 100% and mix well, in a circular lifting motion, before use.
2. Apply 1–2 coats by brush, roller or spray.
3. Allow to dry completely. Average dry time is 4 to 6 hours.
4. Once dry, apply the suitable topcoat paint.

During Painting:
Ensure adequate ventilation. Keep floors and furniture covered.

Coverage:
Coverage rate: approx. 8–10 m²/L per coat.

Disposal:
Do not pour leftover paint in drains or sewers. Keep the unused paint in a covered and sealed container.

Safety and First Aid:

For Spills and Disposal:
Slippery when spilt. Clean up immediately. Do not empty into drains and waterways.

First Aid:
If poisoning occurs, contact your local emergency support.

Eye Contact:
If contact is made with eyes, hold eyes open and flush with running water for at least 15 minutes.

Skin Contact:
If contact is made with skin, remove any contaminated clothing and wash skin with water.

If Swallowed:
Rinse mouth with water. DO NOT induce vomiting.

Validade: 18 meses a partir da data de embalagem.
Best before 18 months from date of packing.

Exported by:
NOWPUREIT

Web: www.brancoforte.com
E-mail: admin@brancoforte.com

Peso líquido / NETT:

Preço máx. / PVP / MRP:

USP:

Lote / BATCH CODE:

Embalado em / PACKED ON: